

RZS462339X





## Details

Xtreme Clutches feature machined pulleys, Cool Coil technology, high performance bearings, stainless steel straps and rivets, Xtreme's Tough Wire Protection System and a replaceable bearing, the Xtreme design is pure performance in every aspect.

- Machined Pulleys CNC machined billet pulleys are stronger, quieter, smoother and maintain stable and faster blade speeds.
- Fatboy Bearings Increased the size of the pulley bearing to imporve bearing life.
- High Temp Bearing Xtreme's special blend of bearing grease is rated more than two times what is required, delivering Xtreme bearing life.
- Triple Protected Wires Every Xtreme clutch has an integrated watertight connection with three layers of protection.
- Replaceable Bearing Xtreme mower clutches have a repaceable pulley bearing!
- Stainless Steel Rivets Xtreme clutches use tough stainless steel brake rivets for long and safe service
- Xtreme "Cool Coil" The "Xtremely Cool Coil " runs over 20% cooler. Electromagnetic clutches run very hot. Most competitive clutches run around 220 degrees. The Xtreme proprietary composite coil runs 175 degrees. The difference is simple: Less heat = ex

## Replaces

R&R Product	S
Scag	

RZS462339 462339

## **GA Power Equipment Spares**

11 Sodium St Narangba, 4504 1300 363 004 https://rgs.rrproducts.com/



# **Clutch - Xtreme Pto Clutch**

RZS462339X

## Specifications

Manufacturer

**Xtreme Equipment** 

### **Fits Models**

Scag SCZ - Cheetah Scag STCII - Tiger Cat II

**GA Power Equipment Spares** 11 Sodium St Narangba, 4504 1300 363 004 https://rgs.rrproducts.com/

